



## Control4® Door Station—Interior

### Control4® Door Station—Interior C4-DSC-EN-INT

The Control4® Door Station-Interior provides an exceptional video and audio intercom experience when combined with other Control4® video-intercom enabled touch screens to provide customers the ability to monitor and communicate with people outside their front doors.

- Delivers H.264 video intercom support when used with the Control4® 7" Portable Touch Screen with Camera or the 7" In-Wall Touch Screen with Camera.
- See who's outside your dwelling from the comfort of your bed or couch when used with Control4® Touch Screens with an integrated camera.
- Easy installation eliminates custom programming and integration of third party devices.
- Exceptional video intercom experience with H.264 full-motion video, integrated speakers, dual microphones with beam forming and wideband audio.
- 2 contacts and 1 relay make it easy to control and monitor doors and gates.
- Audio and video intercom-ready and easily activated with an Intercom license.
- Delivers audio intercom support to Control4® 5" and 7" In-Wall Touch Screens.

## Control4® Door Station—Interior

Model Numbers	C4-DSC-EN-INT
<b>Camera</b>	
Camera	640 x 480 VGA 30 fps Min. illumination: 5 Lux Viewing angle: 120 degrees
<b>Intercom</b>	
Intercom	Full duplex video/audio intercom
Microphone	Dual microphones Voice pickup from 10 feet away Beam forming
<b>Network</b>	
WiFi	IEEE 802.11 b/g/n RF frequency: 2.4 GHz Antenna: connector for external antennas Encryption: 64/128 WEP, TKIP/AES Authentication: WEP, WPA, WPA2
Ethernet	10/100 BaseT Ethernet RJ-45
<b>Power</b>	
Power supply	PoE (IEEE802.3af) 13 W peak AC 100V - 240V, 50-60 Hz DC 12V, 24V
<b>Mounting Options</b>	
Dimensions (H x W x D)	7.25" (183 mm) x 5.25" (133 mm) x 2.5" (63.5 mm)
Mounting	In-Wall
Weight	1.1 lbs. (.49 kg)
Shipping Weight	1.6 lbs. (.725 kg)
<b>Other</b>	
Reset	2 operation modes: Press once to reboot system, or press and hold to restore to its factory default settings.
Operation temperature	For Ethernet operation: -22° F - 149° F (-30° to 65° C) For WiFi operation: -22° F - 122° F (-30° to 50° C) 95% relative humidity
Storage temperature	-49° F - 167° F (-45° C to 75° C)
<b>Accessories</b>	
Intercom License	C4-Intercom-E
Door Station Back Box	C4-DSBB-M
Antenna Kit - WiFi/ZigBee, 2.4 GHz, 26 cm	C4-AK-26cm
Antenna Kit - WiFi/ZigBee, 2.4 GHz, 3 M	C4-AK-3M



Add contacts, relays, motion sensors and touch screens to truly deliver convenience and security throughout the home or office.

**IMPORTANT NOTE:** The Door Station-Interior does not currently function as a stand-alone IP camera. Video access from the Door Station is not available on the current 5" and 7" In-Wall Touch Screens or through the on-screen navigator on a television.

The Door Station-Interior is designed to be mounted in a hallway outside a condo or apartment in a multi-dwelling unit. It is not designed to work in a lobby to communicate with the inhabitants inside the multiple apartments or dwellings. A separate third-party lobby door station would be required for that functionality.

**Also available are the Control4® 5" and 7" In-Wall Touch Screens (audio intercom-capable only) and 7" Portable Touch Screen with Camera (audio and video intercom-capable). For a complete list of Intercom compatibilities, please refer to the Intercom License datasheet.**

Control4™