

# CONTROL4 CA-1 V2

## HUB AND AUTOMATION CONTROLLER



### CONTROL4® CA-1 V2

#### C4-CA1-V2

The Control4® CA-1 V2 Automation Controller is the perfect entry point into Control4 automation built around security, comfort, and convenience. It has built-in control for IP, ZigBee®, and serial devices, plus an internal slot for a Z-Wave Plus™ module (sold separately). It is designed for homeowners, builders, MDUs, and hotels that want smart experiences that include smart lighting, thermostats, door locks, cameras, sensors, shades, and more.

OvrC Pro remote management is built-in, giving you access to the entire network of IP devices, including third-party products. OvrC delivers enhanced troubleshooting capabilities and diagnostic data that makes remote support easy, eliminating unnecessary truck rolls and enabling you to streamline your business and tackle more jobs – all from the OvrC app.

The CA-1 V2 provides the smart home experience homeowners are looking for. It delivers rich, orchestrated automation with the following points of difference:

- The simplest way to experience the Control4 Smart Home
- Orchestrated automation for door locks, shades, cameras, sensors, and lighting
- Built on Control4's proven OS and ecosystem
- Built-in connectivity for IP, ZigBee, and serial devices
- Expansion slot for optional Z-Wave module
- Perfect for broad-scale deployments
- Can be powered by PoE, making it an ideal tool to expand ZigBee in larger Control4 installations
- OvrC Pro built-in for advanced remote management and monitoring

# CONTROL4® CA-1 V2 AUTOMATION CONTROLLER

## Specifications


Model number	C4-CA1-V2
<b>Connections</b>	
Network	Ethernet—10/100BaseT compatible (required for controller setup), PoE supported
ZigBee Pro	802.15.4
ZigBee antenna	External reverse SMA connector
USB port	2 USB 2.0 ports, 500mA
Serial out	1 serial out RJ45 port (RS-232)
Z-Wave	Integrated expansion slot accepts Control4 Z-Wave modules (sold separately)
Z-Wave modules	C4-ZWE, C4-ZWH, C4-ZWU (sold separately)
<b>Power</b>	
Power requirements	5VDC 3A, external power supply included
Power supply	AC power supply accepts 100-240V - 50-60 Hz (0.5A)
PoE	802.3af (<13W)
Power consumption	Max 15W (51 BTU/hr)
<b>Miscellaneous</b>	
Operating temperature	32° - 104°F (0° - 40°C)
Storage temperature	4° - 158°F (-20° - 70°C)
Dimensions (H x W x D)	5.5 x 5.5 x 1.25" (14 x 14 x 3.8 cm)
Weight	0.65 lb (0.3 kg)
Shipping weight	1.5 lb (0.68 kg)

## More info

To access the CA-1 Datasheet, FAQs, and the installation Guide visit [ctrl4.co/ca1v2](http://ctrl4.co/ca1v2)



The Controller Comparison Table illustrates how the CA-1 compares to the other controllers; access it at [ctrl4.co/controller-compare](http://ctrl4.co/controller-compare)



## Dimensions

