

# Control4® Communication Server



Control4® Communication Server  
C4-COMMSERV-PRO  
C4-COMMSERV-LITE

## Communication Server Pro

The Communication Server Pro is based on 2 x Dell PowerEdge servers for reliability and performance. This server is all you need for large MDU projects that require failover support. It is capable of handling anything from 30 to 500 apartments and multiple door stations.



## Communication Server Lite

The Communication Server Lite is based on the Intel® NUC Mini PC and is designed for smaller MDU installs (less than 30 devices). The Lite does not support failover but does have import and export of the configuration for quickly reconfiguring a new server.



## Control4® Communication Server

### Communication Server Pro

<b>Model number</b>	C4-COMMSERV-PRO
<b>Networking</b>	
<b>Ethernet</b>	Broadcom quad-port 1GbE adapter Broadcom dual-port 1GbE adapter
<b>USB port</b>	2 USB 2.0 port—front 2 USB 3.0 port—rear 1 USB 3.0 port—internal
<b>Power</b>	
<b>Power requirements</b>	110-240VAC, 60/50 Hz
<b>Power supply</b>	250W internal power supply
<b>Power consumption</b>	Max: 250W 853 BTUs/hour
<b>Other</b>	
<b>Enclosure</b>	1U rack server
<b>Mounting</b>	ReadyRails™ II sliding rails for tool-less mounting in four-post racks with square or unthreaded round hole or tool-less mounting in four-post threaded hole racks.
<b>Dimensions (H × W × D)</b>	1.75" (44 mm) × 17" (432 mm) × 20" (508 mm)
<b>Operating temperature</b>	32° - 104°F (0° - 40°C)
<b>Storage temperature</b>	4° - 158°F (-20° - 70°C)
<b>Weight</b>	20 lbs (9.1 kg)
<b>Shipping weight</b>	25 lbs (11 kg)

### Communication Server Lite

<b>Model number</b>	C4-COMMSERV-LITE
<b>Networking</b>	
<b>Ethernet</b>	Intel 10/100/1000 Mbps network adapter
<b>USB port</b>	2 USB 3.0 port—front 2 USB 3.0 port—rear
<b>Power</b>	
<b>Power requirements</b>	100-240VAC, 60/50 Hz
<b>Power adapter</b>	19V 65W wall-mount AC power adapter with multi-country plugs
<b>Power consumption</b>	Max: 65W, 222 BTUs/hour
<b>Other</b>	
<b>Mounting</b>	VESA-mount bracket and mounting hole support
<b>Dimensions (H × W × D)</b>	1.2" (32 mm) × 4.3" (111 mm) × 4.5" (115 mm)
<b>Operating temperature</b>	32° - 104°F (0° - 40°C)
<b>Storage temperature</b>	4° - 158°F (-20° - 70°C)
<b>Weight</b>	2.1 lbs (.95 kg)
<b>Shipping weight</b>	2.2 lbs (.99 kg)

For the *Communication Server Setup Guide* and more documentation, visit [ctrl4.co/commserver](http://ctrl4.co/commserver)

