CONTROL4 CORE 1

CONTROLLER



CONTROL4® CORE 1 CONTROLLER

C4-CORE1

Built to be installed behind televisions, CORE 1 enables entertainment and automation experiences in every room. CORE 1 delivers an upgraded 4K HDMI output that provides a beautiful, intuitive, and responsive on-screen user interface with the ability to create and enhance the entertainment experience for any TV. For entertainment, CORE 1 also includes a built-in high-resolution audio server that allows customers to listen to their own music library or stream from a variety of leading music services or from their AirPlay-enabled devices. New DACs (digital to analog converters) and additional audio outputs put the Control4 series of CORE Controllers at the center of our high-resolution audio platform: Ryff.

CORE 1 can orchestrate a wide range of entertainment devices with infrared (IR) and serial (RS-232) control, while providing IP control for network-connected devices for more feature-rich options. CORE 1 also provides secure, wireless control for remotes, lights, thermostats, smart locks, and more through Zigbee. With OvrC Pro built-in, CORE will be the foundation for networking monitoring, management, and remote connections by providing access to the entire network of IP devices, including third-party products. This powerful fusion delivers enhanced troubleshooting capabilities and diagnostic data that makes remote support easy, reduces truck rolls, and improves customer service. View device online status, manage reboots, and quickly add and configure newly discovered devices through the OvrC webpage or mobile app, and provide OvrC Home to customers to empower them with basic troubleshooting capabilities.

- New, updated processors allow CORE 1 to run OS 3 faster and more efficiently, for residential or commercial, with power to spare for new features and functionality currently in development
- Elegant, low-profile design for flexible, simple installation with an included mounting bracket that allows easy mounting to the back of a TV, on the wall, or inside a Versa Box (sold seperately)
- 4K HDMI output paired with an advanced multi-core processor deliver the speed and performance needed for a beautiful, interactive on-screen menu for instantaneous access to video, music, lighting, comfort and security solutions
- Better quality DACs provide 2 zones (HDMI and digital coax) of high-resolution audio with native support for up to 12 streaming services, including Deezer, TIDAL, Pandora, TuneIn, Spotify and SiriusXM, all powered by our high-resolution audio platform: Ryff
- Integrated Power over Ethernet (PoE+) offers single-cable installation for power and network, and enables remote reboot options through OvrC-enabled network switches
- Integrated 2-port Ethernet switch connects CORE 1 and television to the home network without the need to pull an additional network cable or install a network switch
- Included I/O ports (4x IR, 2x serial) and Zigbee antenna provide device control for entertainment, lighting, comfort and security devices
- · USB port enables connection to external hard drives for easy access to local music content
- Built-in OvrC Pro for network monitoring and management, remote connections, and advanced troubleshooting capabilities
- An active 4Sight subscription enables Intercom Anywhere and remote access through the Control4 App for OS 3 through Android and iOS, including Apple Watch, with connection speeds faster than ever



CONTROL4® CORE 1 CONTROLLER

	dded services
Control4 app	Supports up to 50 iOS and Android devices
OvrC Hub	Built-in OvrC Pro functionality
Music Services	Pandora, Napster, Spotify, Tuneln, TIDAL, Deezer, SiriusXM, SOUNDMACHINE, iHeartRadio, Amazon Music, Radio.com, Qobuz
Apple Support	Airplay-enabled devices
Inputs/Outputs - AV	
Video Out	1 video out—HDMI
Video Out	HDMI 2.0a output; 4K @ 60Hz
Audio Out	2 audio out - HDMI, and Digital Coax (output volume control only
Audio Playback	AAC, AIFF, ALAC, FLAC, M4A, MP2, MP3, MP4/M4A, Ogg Vorbis, PCM, WAV, WMA
Audio Resolution	Up to 192 kHz / 24 bit
Inputs/Outputs - Network	
Ethernet	10/100/1000BaseT compatible (required for controller setup) 1 Ethernet/POE+ in port, 1 Ethernet out port
WiFi	Accessory only via USB
WiFi Security	WPA/WPA2
WiFi Antena	Accessory only via USB
Zigbee Pro	802.15.4
Zigbee Antenna	External reverse SMA connector
USB Port	1 USB 3.0 port
Inputs/Outputs - Control	
IR out	4 IR out - 5V 27ma max output
IR capture	1 IR receiver—front; 20-60 kHz
Serial out	2 serial out (shared with IR out 1 and 2)
	Power
Power requirements	100-240VAC, 60/50Hz POE+
Power consumption	Max: 18W, 61 BTUs/hour Idle: 12W, 41 BTUs/hour
	Other
• "	70 1015 (0 10 0)
Operating temperature	32 - 104 F (0 - 40 C)
Storage temperature	4 - 158 F (-20 - 70 C)
Storage temperature Fan dB level	4 - 158 F (-20 - 70 C) No fan
Storage temperature Fan dB level Wall Mount Bracket	4 - 158 F (-20 - 70 C) No fan Yes - separate
Storage temperature Fan dB level Wall Mount Bracket Rack Mount Kit	4 - 158 F (-20 - 70 C) No fan Yes - separate Yes - separate
Storage temperature Fan dB level Wall Mount Bracket Rack Mount Kit Feet	4 - 158 F (-20 - 70 C) No fan Yes - separate Yes - separate Yes - included
Storage temperature Fan dB level Wall Mount Bracket Rack Mount Kit Feet Other - Mech	4 - 158 F (-20 - 70 C) No fan Yes - separate Yes - separate Yes - included nanical and Hardware
Storage temperature Fan dB level Wall Mount Bracket Rack Mount Kit Feet	4 - 158 F (-20 - 70 C) No fan Yes - separate Yes - separate Yes - included
Storage temperature Fan dB level Wall Mount Bracket Rack Mount Kit Feet Other - Mech	4 - 158 F (-20 - 70 C) No fan Yes - separate Yes - separate Yes - included manical and Hardware Status LEDs (listed left to right): music streaming, warning, link,
Storage temperature Fan dB level Wall Mount Bracket Rack Mount Kit Feet Other - Mech	4 - 158 F (-20 - 70 C) No fan Yes - separate Yes - separate Yes - included Manical and Hardware Status LEDs (listed left to right): music streaming, warning, link, power
Storage temperature Fan dB level Wall Mount Bracket Rack Mount Kit Feet Other - Mech	4 - 158 F (-20 - 70 C) No fan Yes - separate Yes - separate Yes - included nanical and Hardware Status LEDs (listed left to right): music streaming, warning, link, power Includes LED that mimics the power LED on the front panel
Storage temperature Fan dB level Wall Mount Bracket Rack Mount Kit Feet Other - Mech	4 - 158 F (-20 - 70 C) No fan Yes - separate Yes - separate Yes - included manical and Hardware Status LEDs (listed left to right): music streaming, warning, link, power Includes LED that mimics the power LED on the front panel i.MX8Mi
Storage temperature Fan dB level Wall Mount Bracket Rack Mount Kit Feet Other - Mech Front Panel LEDs ID Button CPU RAM	4 - 158 F (-20 - 70 C) No fan Yes - separate Yes - separate Yes - included Manical and Hardware Status LEDs (listed left to right): music streaming, warning, link, power Includes LED that mimics the power LED on the front panel i.MX8Mi 2GB Minimum

For product photos, documentation, and installation instructions, visit ctrl4.co/controllers

ONLINE PORTAL-CONTROLLERS -



