

R20 SERIES

IN-CEILING R25, R26, R28, R28DT OPEN ROUNDS



TRIAD R20 SERIES

R25, R26, R28, R28DT OPEN ROUNDS

Triad's R20 series in-ceiling speakers are engineered for music enthusiasts that are looking for exceptional sound in every room. The series utilizes carbon fiber woofers for superior bass response and durability. A one-inch silk dome tweeter offers smooth, high-frequency sound and is aimable to offer greater installation flexibility.

The R20 series is voice-matched—allowing homeowners to choose the right size speaker for each room while delivering identical tonal qualities throughout the home.

The R28DT incorporates dual tweeters into a single speaker enclosure, making it the perfect choice for delivering stereo sound into smaller rooms.

R20 speakers ship with white, round, microframe grills that are low profile and look great. They utilize embedded magnets for fast installation and a snug fit. Custom paint matched round or square grills are available separately and painted at the factory for a perfect finish that blends seamlessly with any interior design.

MATERIALS

- Carbon fiber woofers
- 1" silk dome tweeters
- High-quality crossover

FEATURES

- Open back, two-way design
- Aimable 1" (25 mm) tweeter
- Tweeter adjustment switch (+/- 3 dB)
- Round grill included
- Square grill sold separately
- Custom paint finishes for round or square grills available (standard grill finish is white)

TRIAD R20 SERIES R25, R26, R28, R28DT OPEN ROUNDS

SPECIFICATIONS

	MATERIALS	R25	R26	R28	R28DT
Tweeter size		(1) 1" (25 mm)	(1) 1" (25 mm)	(1) 1" (25 mm)	(2) 1" (25 mm)
Tweeter type		Silk dome	Silk dome	Silk dome	Silk dome
Woofer size		(1) 5 1/4" (14 cm)	(1) 6 1/2" (17 cm)	(1) 8 1/2" (22 cm)	(1) 8 1/2" (22 cm)
Woofer type		Carbon fiber	Carbon fiber	Carbon fiber	Carbon fiber
	PERFORMANCE	R25	R26	R28	R28DT
Recommended amplifier power		25 - 125W	25 - 125W	25 - 125W	100W max
Impedance		8 ohm	8 ohm	8 ohm	8 ohm
Sensitivity (dB @ 2.83V, 1 m)		86 dB	87 dB	88 dB	87 dB
Frequency response (+/- 3 dB)		68 Hz - 20 kHz	50 Hz - 20 kHz	40 Hz - 20 kHz	40 Hz - 20 kHz

	DIMENSIONS	R25	R26	R28	R28DT
Inside ring diameter		6 3/8" (16.2 cm)	7 3/4" (19.6 cm)	9 7/16" (23.9 cm)	9 7/16" (23.9 cm)
Mounting depth		3 3/4" (9.5 cm)	4" (10.1 cm)	4 3/8" (11.1 cm)	4 3/8" (11.1 cm)
Hole cut out (diameter)		6 1/2" (16.5 cm)	7 7/8" (20.0 cm)	9 1/2" (24.1 cm)	9 1/2" (24.1 cm)
NCB size		R5	R6	R8	R8
Grill (diameter)		8 5/16" (21.1 cm)	9 11/16" (24.6 cm)	11 5/16" (28.7 cm)	11 5/16" (28.7 cm)
Product weight (pair)		7.36 lb (3.34 kg)	8.33 lb (3.78 kg)	9.0 lb (4.10 kg)	5.0 lb (2.3 kg)
Shipping weight (pair)		10.5 lb (4.75 kg)	12.23 lb (5.55 kg)	13.8 lb (6.26 kg)	7.5 lb (3.4 kg)

PRODUCT PAGE



PRODUCT NUMBERS

	R25 (pair)	R26 (pair)	R28 (pair)	R28DT (each)
R20 In-Ceiling Round	50250-1	50260-1	50280-1	50285-1
Round Metal Grill	006-0250	006-0260	006-0280	006-0280
Round Metal Grill Custom	006-0250C	006-0260C	006-0280C	006-0280C
Square Metal Grill	006-0251	006-0261	006-0281	006-0281
Square Metal Grill Custom	006-0251C	006-0261C	006-0281C	006-0281C

DIMENSIONS

