# **CONTROL4® VIBRANT**

#### PERFORMANCE RGBTW LINEAR LIGHT



### CONTROL4 VIBRANT PERFORMANCE RGBTW LINEAR LIGHT

#### C4-LP-RGBTW-13

#### C4-LP-RGBTW-98

Provide intense color saturation, transition effects, and fade-to-white lighting effects with RGB + Tunable CCT linear lighting - the ultimate color-changing solution. With a virtually unlimited RGB palette of color combinations, this tape light adjusts true white light ranging from 1800K up to 6000K for the ideal lighting effect (Note: when used with Creative or Axxess Lighting products).

- Dynamic RGB+Tunable CCT color mixing capabilities
- Create millions of color combinations for impactful installations
- Features 3-in-1 RGB LEDs with alternating 2700K & 6000K LEDs
- Lumen output ranging up to 410 Lumens per foot
- Measures 12 mm wide and is cuttable every 3.94" (100 mm) with 13.1ft max run
- Easy installation featuring 3M VHB adhesive backing
- IP54 rating featuring a nano-coating protective layer
- Control for color change and dimming via DMX/DALI (requires Creative Lighting Gateway) or Zigbee (requires Axxess DCM module)
- cULus Listed for indoor dry/damp locations
- 50,000 hours rated life




## CONTROL4® VIBRANT PERFORMANCE RGBTW LINEAR LIGHT

# QUICK LOOK Alternating RGB and tunable white LEDs 12 mm (0.46") wide



– 13.1 ft (4 m) max run

#### QUICK CONNECTION



#### **SPECIFICATIONS**

Model number	C4-LP-RGBTW-13 C4-LP-RGBTW-98
Power requirements	24V DC This device requires a neutral connection
Wattage	7W / ft (0.3 m)
Lumens	Up to 410Lm / ft (0.3 m)
Max run	13 ft (4 m)
Color temperature	RGB + 2700-6000K
CRI	90+
Beam angle	120 °
Tape size	0.46" (12 mm) W × 0.06" (1.65 mm) H
Cutting increment	3.94" (100 mm)
Control method	24V Power Supply with DMX Reciever
Dimming compatability	DMX controlled dimming
Operational temperature	0° C to 40° C (32° F to 104° F)
Humidity	5% to 95% non-condensing
Storage	-20° C to 60° C (-4° F to 140° F)
IP rating	IP54 suited for indoor dry and damp locations





